

The Product Range

The Subconn® product range can be divided into 5 groups as indicated in the index.

- Standard Circular series with up to 16 contacts
- Standard Low Profile series with up to 9 contacts
- Micro series with up to 16 contacts
- Metal Shell series with up to 12 contacts
- Special connectors including single & three phase Power, Hermaphroditic, SplitConn, Reed switches & AddConn connectors

Ordering information

In order to simplify enquiries and the ordering of connectors we have included drawings and code numbers of all the currently available connectors. There are, however, a number of options available and these should be noted with any enquiry or purchase order. These include:

- Non-standard inline cable or bulkhead lead length
- Special cable requirements
- Gold plated Mil. Spec. contacts
- Nut & washer sets for bulkhead connectors
- Stainless steel AISI 316, NiAlBr and titanium bulkhead bodies
- Brass, stainless steel and titanium locking sleeves
- Non-standard bulkhead threads and lengths
- Special harness cable requirements including penetrators
- Stress terminations to electro-mechanical cables
- Certified electrical, pressure and stress tests
- Specially engineered connectors based on the Subconn® principle
- All Penetrators

Connectors

		LP	BH	RA	2	F	SS	GP
LP	Low profile	_____						
MC	Micro							
HP	High power							
RS	Reed switch							
BH	Bulkhead		_____					
IL	Inline							
OM	Overmould							
AT	Attachable							
DC	Dummy							
PBOF	Pressure balanced oil filled							
RA	Right angle			_____				
S	SplitConn							
V	VentConn							
B	Battery							
M	Mini							
2	No. of contacts				_____			
F	Female socket					_____		
M	Male pin							
H	Hermaphroditic							
SS	Stainless steel body						_____	
GP	Gold plated pins							_____

Locking Sleeves

		DLS	A	F
DLS	Delrin	_____		
BLS	Brass			
MCDLS	Micro Delrin			
SSLS	Stainless steel			
A	2, 3, 4 & 5 contact		_____	
	Micro 10, 12 & 16 contact			
B	1, 6, 8 & 10 contact			
C	12 & 16 contact			
F	½ pair female			_____
M	½ pair male			
H	½ pair hermaphroditic			
-	Complete pair			

Metal Shell Connectors

		BCR	2004	F
BCR	Bulkhead connector receptable	_____		
FCR	Flange connector receptable			
20xx	Shell size (Series)		_____	
xx04	No. of pins /sockets			
F	Female socket			_____
M	Male pin			

Locking Sleeves

		LS	2000
LS	Delrin	_____	
SSLS	Stainless steel		
2000	Shell size (Series)		_____

1500 metal series uses MCDLS locking sleeves

